

AKIN GUMP
STRAUSS HAUER & FELD LLP

Attorneys at Law

FAX TRANSMISSION

June 6, 2003

Total number of sheets including cover: 7

NAME	COMPANY	FAX	PHONE
Mail Stop No Fee AF	PTO	703.872.9319	

From: Richard A. Schafer

Direct Dial: 713.220.8184

Fax: 713.236.0822

Re: 053310.0097

Message: Request for Reconsideration

#9/B
7/7/03
sum.
(no)

04890 807

FAX RECEIVED

JUN 06 2003

TECHNOLOGY CENTER 2800

entered
RCE
DS mails-104
8/25/03

5 30

053310.0097

136R1

Secretary M Mingu

Ext. 18173

Return fax via Interoffice Mail

Hold fax for pickup

Fax Operation Verification

WFO

The information contained in this facsimile message is attorney-client privileged and confidential, and is intended only for the use of the individual or entity named above. If the reader of this message is not the intended recipient, or the employee or agent responsible to deliver it to the intended recipient, you are hereby notified that any dissemination, distribution or copying of this communication is strictly prohibited. If you have received this communication in error, please notify us immediately by telephone, and return the original message to us by mail at the address below.

1900 Pennzoil Place - South Tower / 711 Louisiana Street / Houston, Texas 77002 / 713.220.5800 / fax: 713.236.0822 / www.akingump.com

Received from <7132360822> at 6/6/03 6:31:24 PM [Eastern Daylight Time]

AMENDMENTS

Please amend claim 1.

A complete list of the pending claims follows:

B!

1. (Currently Amended) A connector for interconnecting or mutually isolating two or more circuits, comprising first and second interengageable connector elements each of which is connected in use to a respective circuit and at least one of which supports a first contact connected to the respective circuit and a displaceable contact holder carrying interconnected second and third contacts, the contact holder being displaceable between a first position in which the first and second contacts are separated and a second position in which the first and second contacts are interconnected, wherein the connector elements are formed such ^{locking} ~~comprise~~ means for ensuring that on interengagement the contact holder is displaced from the first to the second position after the third contact is interconnected with a contact of the other connector element, ~~and such~~ ^{locking} the connector elements comprise means for ensuring that on disengagement the contact holder is displaced from the second to the first position, ~~the contacts being arranged such~~ and the connector elements comprise means for ensuring that on disengagement the first and second contacts separate before the third contact is separated from the said contact of the other connector element and such that when separated the first and second contacts are located within a closed chamber defined within the said at least one connector element, ^{said} means being provided for locking the or each contact holder to ~~the~~ the said contact of the other connector elements unless the first and second contacts are separated.

2. (Original) A connector according to claim 1, wherein each connector element supports a respective first contact and a respective displaceable contact holder carrying interconnected second and third contacts such that on interengagement of the connector elements the third contacts are interconnected.

3. (Previously Amended) A connector according to claim 1, wherein means are provided to prevent the contact holder from being blown out of the associated connector element.

4. (Original) A connector according to claim 3, wherein the preventing means comprises a pin received in a slot formed in the contact holder.

5. (Previously Amended) A connector according to claim 1, wherein the contact holder is slidable in a bore such that the closed chamber is defined between the contact holder and walls of the bore.

6. (Previously Amended) A connector according to claim 1, wherein the means for locking the contact holder to the said contact of the other connector elements comprise one or more locking balls which are retained in locking engagement between the connector element and the contact holder unless the contact holder is in the first position.

7. (Previously Amended) A connector according to claim 1, comprising means for locking the contact holder in the first position when the contact elements are separated.

8. (Previously Amended) A connector according to claim 7, wherein the locking means maintain the contact holder in the first position unless the contact elements are interengaged.

9. (Previously Amended) A connector according to claim 8, wherein the locking means comprise a spring-biased slider displaceable as a result of interengagement of the connector elements from one position in which it retains one or more locking balls in locking engagement between the connector element and the contact holder with the contact holder in the first position and a further position in which the locking ball is released and the contact holder is displaceable to the second position.

10. (Cancelled).

11. (Original) A connector according to claim 2, wherein means are provided to prevent each contact holder from being blown out of the associated connector element.

12. (Original) A connector according to claim 11, wherein the preventing means comprises a pin received in a slot formed in the contact holder.

B'
cont.